Visual Evaluation of Soil Structure (VESS)

Soil structure affects root penetration, water availability to plants and soil aeration. This simple, quick test assesses soil structure based on the appearance and feel of a block of soil dug out with a spade. The scale of the test ranges structure quality from Sq1, good structure, to Sq5, poor structure.



Equipment

Garden spade approx. 20 cm wide, 22-25 cm long.

Optional: light-coloured plastic sheet, sack or tray approx. 50 by 80 cm, small knife, digital camera.



When to sample

Any time of year, but preferably when the soil is moist. If the soil is too dry or too wet it is difficult to obtain a representative sample. Roots are best seen in an established crop or for some months after harvest.



Where to sample

Select an area of uniform crop or soil colour or an area where you suspect there may be a problem. Within this area, plan a grid to look at the soil at 10, preferably more, spots. On small experimental plots, it may be necessary to restrict the number to 3 or 5 per plot.

With the kind permissions of Dr Bruce C Ball (SRUC), Dr Rachel Guimarães (University of Maringá (Brazil) and Dr Paul Hargreaves (SRUC).

Step by step











Authors: Dr Bruce C Ball (SRUC), Dr Rachel Guimarães (University of Maringá, Brazil), Dr Paul Hargreaves (SRUC), Tom Batey (Independent Consultant), Lars Munkholm (University of Aarhus, Denmark). Photos by Bruce C Ball and Lars Munkholm. Layout by Ben, "de la graine à l'humus" (France), icons by "font Awesome".

Method of assessment

A video by agroscopevideo (Visual Evaluation of Soil Structure - VESS method) details the method.

Step	Option	Procedure				
Block extraction and e	xamination					
Extract soil block	Loose soil	Remove a block of soil \sim 15 cm thick directly to the full depth of the spade and place spade plus soil onto the sheet, tray or the ground.				
	Firm soil	Dig out a hole slightly wider and deeper than the spade leaving one side of the hole undisturbed. On the undisturbed side, cut down each side of the block with the spade and remove the block as above.				
2. Examine soil block	Uniform structure	Remove any compacted soil or debris from around the block.				
	Two or more horizontal layers of differing structure	Estimate the depth of each layer and prepare to assign scores to each separately.				
Block break-up 3. Break up block (take a photograph - optional)		Measure block length and look for layers. Gently manipulate the block using both hands to reveal any cohesive layers or clumps of aggregates. If possible separate the soil into natural aggregates and man-made clods. Clods are large, hard, cohesive and rounded aggregates.				
Break up of major aggregates to confirm score		Break larger pieces apart and fragment it until a piece of aggregate of 1.5 - 2.0 cm. Look to their shape, porosity, roots and easily of break up. Clods can be broken into non-porous aggregates with angular corners and are indicative of poor structure and higher score.				
Soil scoring		If the block contains the subsoil, evaluate the subsoil separately with the SubVESS chart.				
5. Assign score		Match the soil to the pictures category by category to determine which fits best.				
6. Confirm score from:	Block extraction	Difficulty in extracting the soil block.				
	Aggregate shape and size	Larger, more angular, less porous, presence of large worm holes.				
	Roots	Clustering, thickening and deflections.				
	Anaerobism	Pockets or layers of grey soil, smelling of sulphur and presence of ferrous ions.				
	Aggregate fragmentation	Break up larger aggregates $\sim 1.5-2.0$ cm of diameter fragments to reveal their type.				
7.Calculate block scores for two or more layers of differing structure	5	Multiply the score of each layer by its thickness and divide the product by the overall depth, e.g. for a 25 cm block with 10 cm depth of loose soil (Sq1) over a more compact (Sq3) layer at 10-25 cm depth, the block score is $(1 \times 10)/25 + (3 \times 15)/25 = $ Sq 2.2				

Scoring

- Scores may fit between Sq categories if they have the properties of both.
- Scores of 1-3 are usually acceptable whereas scores of 4 or 5 require a change of management.

VESS chart : Structure quality	Size and appearance of aggregates	Visible porosity and roots	Appearance after break-up: various soils	Appearance after break-up: same soil different tillage	Distinguishing feature	Appearance and description of natural or reduced fragment	0- 1-
Sq1 Friable Aggregates readily crumble with fingers	Mostly < 6 mm after crumbling.	Highly porous. Roots throughout the soil.			Fine aggregates	The action of breaking the block is enough to reveal them. Large aggregates are composed of smaller ones, held by roots.	0- 1- 2- 3- 4-
Sq2 Intact Aggregates easy to break with one hand	A mixture of porous, rounded aggregates from 2mm - 7 cm. No clods present.	Most aggregates are porous. Roots throughout the soil.			High aggregate porosity	Aggregates when obtained are rounded, very fragile, crumble very easily and are highly porous.	
Sq3 Firm Most aggregates break with one hand	A mixture of porous aggregates from 2mm -10 cm; less than 30% are <1 cm. Some angular, non-porous aggregates (clods) may be present.	Macropores and cracks present. Porosity and roots both within aggregates.			Low aggregate porosity	Aggregate fragments are fairly easy to obtain. They have few visible pores and are rounded. Roots usually grow through the aggregates.	1 <u>0</u>
Sq4 Compact Requires considerable effort to break aggregates with one hand	Mostly large > 10 cm and sub-angular non- porous; horizontal/ platy also possible; less than 30% are <7 cm.	Few macropores and cracks. All roots are clustered in macropores and around aggregates.			Distinct macropores	Aggregate fragments are easy to obtain when soil is wet, in cube shapes which are very sharp-edged and show cracks internally.	
Sq5 Very compact Difficult to break up	Mostly large > 10 cm, very few < 7 cm, angular and non- porous.	Very low porosity. Macropores may be present. May contain anaerobic zones. Few roots, if any, and restricted to cracks			Grey-blue colour	Aggregate fragments are easy to obtain when soil is wet, although considerable force may be needed. No pores or cracks are visible usually.	- I I ma